



US006196311B1

(12) **United States Patent**  
**Treece**

(10) Patent No.: **US 6,196,311 B1**  
(45) Date of Patent: **Mar. 6, 2001**

(54) **UNIVERSAL CEMENTING PLUG**

(75) Inventor: **Harold O. Treece, Duncan, OK (US)**

(73) Assignee: **Halliburton Energy Services, Inc.,  
Duncan, OK (US)**

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/175,664**

(22) Filed: **Oct. 20, 1998**

(51) Int. Cl.<sup>7</sup> ..... **E21B 33/16**

(52) U.S. Cl. .... **166/192**

(58) Field of Search ..... **166/192, 290,  
166/154, 289, 153, 155, 291, 193, 194**

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

3,605,896	9/1971	Perkins	166/290
3,616,850	11/1971	Scott	166/155
3,768,556	10/1973	Baker	166/154
3,768,562	10/1973	Baker	166/289
3,796,260	3/1974	Bradley	166/153
3,948,322	4/1976	Baker	166/289
4,246,967	1/1981	Harris	166/291
4,246,968	1/1981	Jessup et al.	166/334
4,624,312	11/1986	McMullin	166/155
4,836,279	6/1989	Freeman	166/153
4,858,687	8/1989	Watson et al.	166/153
4,934,452	6/1990	Bradley	166/153
5,095,980	3/1992	Watson	166/192
5,437,330	8/1995	Gambertoglio	166/289
5,533,570	7/1996	Streich et al.	166/153
5,722,491	3/1998	Sullaway et al.	166/291
5,813,457	9/1998	Giroux et al.	166/153

**FOREIGN PATENT DOCUMENTS**

0 371 576 A1 6/1990 (EP).

0 498 990 A1 8/1992 (EP).  
0 697 496 A2 2/1996 (EP).  
0 774 564 A2 5/1997 (EP).  
0 869 257 A2 10/1998 (EP).  
2 663 678 A1 12/1991 (FR).

**OTHER PUBLICATIONS**

Halliburton Services Sales & Service Catalog No. 44, pp. 26-30 and 48-52 (1990).

Primary Examiner—Christopher J. Novosad

(74) Attorney, Agent, or Firm—Craig W. Roddy; Neal R. Kennedy

(57) **ABSTRACT**

A cementing plug having a universal construction and improved wiping and extended wear characteristics. The cementing plug has a plug subassembly with a body member and an elastomeric jacket on the body member. The body member defines a central opening therethrough with a shoulder therein. To configure the plug as a bottom cementing plug, a shearable insert is positioned on the shoulder, and to configure the plug as a top cementing plug, a non-shearable insert is positioned on the shoulder. The shearable insert is one of a plurality of such inserts designed to shear at correspondingly different shear pressures. In a first embodiment, the shearable insert is a substantially flat disk having a uniform thickness, and in a second embodiment, the shearable insert has an outer ring portion and a relatively thin inner domed portion. Thus, a bottom plug may be pumped down a well casing with cement and a top plug thereabove so that when the bottom plug lands at the bottom of the casing, the shearable insert will shear at the predetermined pressure. The jacket has one or more wiper cups which have a conical surface extending at an acute angle with respect to a longitudinal axis of the plug, thereby providing a substantially large contact area in the well casing to improve wiping efficiency and extend life.

**51 Claims, 2 Drawing Sheets**

